## **Mobile Home Data**

Manufacturer:		_Year:	Mode	:l:	
Size: Length:x Width:	_No. of Units:_		Actual Fl	oor Area:	
MH Insignia Number (HUD sticker no.):					
MH Serial Number(s):	_x		x		
Roof Live Load:	_p.s.f. Wind I	Load:			p.s.f.
Electrical Service:	_ampacity	Gas Ris	er Size:		
Water Supply:	_inches	Drain:			inches
<b>Note:</b> Flex connectors required for all piping at the Exception: MH installed I.A.W. 18551 H & S.	e union of site r	isers and	MH piping i	nstalled in the v	vertical portion
Load and Bearing Support (Columns)					
Manufactured by:	Manufactured by:Listed a			y:	lbs.
Field Assembled Supports, capacity					lbs.
Footing Materials (Column Pads or Base)					
2 x pressure-treated lumber: Size	x	_Capacity	/		lbs.
3-1/2-inch min. thickness concrete: Size	x	_Capacity	/		lbs.
Note: Allowable soil-bearing pressure without a lice foot.  Tiedowns (required for all Mobile Homes)	censed Californ	iia Engine	ers Soil Rep	ort is 1,000 lbs	s. per square
Required Manufacturer			Rated	d Capacity:	lbs.
Spacing			ft. N	umber per side	9:
Flood zone, both frame and over-the-top tiedowns	required.				
Perimeter Supports					
Required spacing not more than		f	t		_inches apart
Main Frame Supports					
Spaced not more than		f	t		_inches apart
Sizex			Сара	city	lbs.
Marriage Line Supports					
Number required:from t	he tongue end	to the rea	r, i.e., A, B,	C, D, E, F, G, I	H, I, J
Albsfeetind	ches B.	ļ	bsfe	etinche	s S
Clbsfeetind	ches D.	<u> </u>	bsfe	etinche	s S
Elbsfeetind	ches F.	l	bsfe	etinche	es
Glbsfeetind	ches H.	l	bsfe	etinche	es
Ilbsfeetind	ches J	l	bsfe	etinche	es
Site Elevation					
Signature of Applicant				Date	
Approved by:		(Building Inspector) Date			